COMMUNICATIONS RESOURCE AVAILABILITY WORKSHEET										Frequency Band **HF (3 - 30 MHz)**	Description **SSB**
	Channel Configuration	Channel Name/Trunked Radio System Talkgroup	Eligible Users	RX Freq	N or W	RX Tone/NAC	TX Freq	N or W	Tx Tone/NAC	Mode A, D or M	Remarks
1	Simplex	N/A	Amateur	3.9900	N/A	N/A	3.9900	N/A	N/A	A	Primary
2	Simplex	N/A	Amateur	3.9730	N/A	N/A	3.9730	N/A	N/A	A	Secondary
3	Simplex	N/A	Amateur	7.2520	N/A	N/A	7.2520	N/A	N/A	A	Primary
4	Simplex	N/A	Amateur	7.2320	N/A	N/A	7.2320	N/A	N/A	A	Secondary
5	Simplex	N/A	Amateur	14.2250	N/A	N/A	14.2250	N/A	N/A	A	General band - low limit
6	Simplex	N/A	Amateur	14.3500	N/A	N/A	14.3500	N/A	N/A	A	General band - high limit

The convention calls for frequency lists to show four digits after the decimal place, followed by either an "N" or a "W", depending on whether the frequency is narrow or wide band. Mode refers to either "A" or "D" indicating analog or digital (e.g. Project 25) or "M" indicating mixed mode. All channels are shown as if programmed in a control station, mobile or portable radio. Repeater and base stations must be programmed with the Rx and Tx reversed.